W WM SERIES



FFATURES

72

- 19" EIA 310-D Compliant
- Horseshoe knockouts on the top and bottom of the enclosure allow already configured patch panels to be installed
- 2 pair of #12-24 rails; fully adjustable
- Solid Steel or Plexiglas Doors
- 1, 2, and 3" conduit and horseshoe knockouts on top and bottom of rear section; 1, 2, and 3" on rear section
- Full piano hinge provides added strength for rear section
- Dust Kit available to protect equipment in high dust/industrial areas
- Center swing-out section provides front/rear access to cables
- · Reversible cabinet for left or right hand swing-out
- Vented side panels for air flow
- Weight tested to ½" of deflection

WM SERIES

PART NO. DESCRIPTION

GL2418WM 24"H x 21.25"W x 18"D, Usable depth 16", Maximum rail

spacing 11.06", 12 RMU, Plexiglas door

Weight capacity 150 lbs.*, Shipping wt. 85 lbs.

GL2418WMS Same as GL2418WM except solid door

GL24WM 24"H x 21.25"W x 24.5"D, Usable depth 22", Maximum rail

spacing 17.62", 12 RMU, Plexiglas door

Weight capacity 150 lbs.*, Shipping wt. 95 lbs.

GL24WMS Same as GL24WM except solid door

GL36WM 36"H x 21.25"W x 24.5"D, Usable depth 22", Maximum rail

spacing 17.62", 19 RMU, Plexiglas door

Weight capacity 250 lbs.*, Shipping wt. 125 lbs.

GL36WMS Same as GL36WM except solid door

GL48WM 48"H x 21.25"W x 24.5"D, Usable depth 22", Maximum rail

spacing 17.62", 25 RMU, Plexiglas door

Weight capacity 300 lbs.*, Shipping wt. 160 lbs.

GL48WMS Same as GL48WM except solid door

ACCESSORIES

7219 6 position Power Strip for 19" mounting;

5-15R receptacle and 5-15P plug

7219-SR14 14 position (6 front/8 back) Power Strip for 19" mounting;

5-15R receptacle and 5-15P plug with surge protector

7206-14 Stationary Shelf, 17.5"W x 14"D, 80 lb. weight capacity

(for use with GL2418)

7206-EIA Stationary Shelf, 17.468"W x 18"D, 80 lb. weight capacity

7206-FR-A18 Stationary Shelf (front/rear mount adjustable),

17.5"W x 18"D, 150 lb. weight capacity

7206-SL Sliding Shelf, 16.343"W x 17.5"D, 40 lb. weight capacity

CBB-19 Copper Bus Bar for 19" mounting (isolated)

GR102 Grounding Kit for use with WM, WD, WS, and WE

Wall Mounts

7217WS Fan Assembly with Fan Guards and two 75 CFM fans

FFK1 Four Fan Filters

DK2 Dust Resistant Kit; includes 4 cover plates, 4 fan filters

and hardware (not for use with GL2418)

^{*}All maximum weight capacities determined at minimal deflection.