E GL720E-2936 SERIES



DIMENSIONS: 72"H x 29"W x 36"D Maximum rail placement and usable inside depth: 34"

RACK SPACES: 37 RMU · 19" EIA 310-D Compliant

STOCK COLORS: Black, Advantage White, or Nitro Blue

WEIGHT CAPACITY:

1500 lbs. on levelers, bolted to floor, or on heavy duty casters

SHIPPING WEIGHT AND PALLET SIZE: 350 lbs./78"H x 32"W x 38"D

| GL720E-2936P | COMPLETE ENCLOSURE INCLUDES PARTS BELOW | |
|-------------------------------|---|--|
| PART NO. 7201E-2936 | DESCRIPTION Frame with two pairs of black powder coated, universal 19" M6 mounting rails (with RMU markings) and package of M6 hardware | |
| 7209-N | One Set of 4 Adjustable Levelers (2.5"H) | |
| TPE-29P | Removable Vented Top Panel With two 4" horseshoe knockouts | |
| 7202E-29 | Plexiglas Front Door with locking swing handle | |
| 7204E-29 | Perimeter Vented Steel Rear Door with locking swing handle | |
| 7210-36ELS | Pair of Solid Lift-off Side Panels with lock and finger release latches | |
| 7215 | 16 position, 15 amp Power Strip; 5-15R receptacle and 5-15P plug | |
| ADDITIONAL CONFIGURATIONS | | |

GL720E-2936F Complete enclosure with TPE-29F (top panel with three 75 CFM fans) GL720E-2936F10 Complete enclosure with TPE-29F10 (top panel with one 10", 550 CFM fan)

GL720E-2936S Complete enclosure with TPE-29S solid top

Shown with optional accessories, drawings can be found on page 138

GL720E-2936 ACCESSORIES E

PART NO. DESCRIPTION

| DOORS & SIDE FANELS | | |
|---------------------------------|---|--|
| 7202E-29PV | Perimeter Vented Plexiglas Door | |
| 7203E-29 | Solid Door | |
| 7202E-M29 | Mesh Steel Door | |
| 7211-36ELL | Pair of Locking Lift-off Vented Side Panels | |
| Additional Doors, pages 100-103 | | |

TOP & BOTTOM PANELS

| TPE-29F | Top Panel and Fan Assembly with two |
|-----------------------|--|
| TPE-29F10 | 4" horseshoe knockouts Top Panel and Fan Assembly with one 10", |
| | 550 CFM fan |
| BPF29 | Bottom Panel (Filtered), 13"W x 16"D; |
| | includes rear solid panel |
| BPS29 | Bottom Panel (Solid), 13"W x 16"D; |
| | includes rear solid panel |
| Additional Tan and De | ttom Danala nagaa 107 109 |

Additional Top and Bottom Panels, pages 107-108

CABLE MANAGEMENT

| VLB-7236 | Vertical Lacing Bar Kit (includes 1 vertical bar, |
|----------|---|
| | 2 horizontal bars and 6 cinch straps) |
| HLB-36 | Horizontal Lacing Bar for 36"D enclosure |
| VLB-72 | Vertical Lacing Bar for 72"H enclosure |
| | (includes 6 cinch straps) |
| HCM-D36 | Front to rear horizontal cable manager |

19" RACK MOUNT CABLE MANAGEMENT

CM-15Double-sided Cable Organizer with plastic fingers
and covers, 2 RMUCM-16Single-sided Cable Organizer with plastic fingers
and covers, 1 RMU

Additional Cable Management, pages 123-130

STATIONARY SHELVES FOR 19" MOUNTING

| 7206-FR-AHD | Front/Rear Mount adjustable, | 17.5"W x 22.25"D, |
|---------------|--|-------------------|
| | 200 lb. weight capacity | |
| 7206-FR-ADHD | Front/Rear Mount adjustable, | 17.5"W x 27.25"D, |
| | 150 lb. weight capacity | |
| 7206-FR-A32HD | Front/Rear Mount adjustable, | 17.5"W x 32"D, |
| | 300 lb. weight capacity | |
| | 150 lb. weight capacity Front/Rear Mount adjustable, | |

SLIDING & SPECIALTY SHELVES FOR 19" MOUNTING

| 7206-FRSL-AHD | Front/Rear Mount adjustable, 17.5"W x 22"D, |
|------------------------|--|
| | 110 lb. weight capacity |
| 7206-FRSL-ADHD | Front/Rear Mount adjustable, 17.5"W x 26"D, |
| | 110 lb. weight capacity |
| 7206-FRSLA300 | Front/Rear Mount adjustable, 14.33"W x 30"D, |
| | 300 lb. weight capacity |
| 7206-MKM | Monitor/Keyboard/Mouse Shelf |
| 7206-PKB-MT | Pivoting Keyboard Tray with Mouse Tray |
| Additional Shelves, pa | ages 110-111 |
| | |

POWER STRIPS, COPPER BUS BAR, & COOLING EQUIPMENT

| 7215-S | 16 position, 15 amp Power Strip (with surge suppressor); |
|--------------|--|
| | 5-15R receptacle and 5-15P plug |
| 7215-20ARTLP | 16 position, 20 amp Power Strip; |
| | 5-20R receptacle and L5-20P plug |
| 7215-20AR | 16 position, 20 amp Power Strip; |
| | 5-20R receptacle and 5-20P plug |
| CBB-60 | Copper bus bar 58" (isolated) |
| 7217FT-3 | Fan Tray (Front/Rear Mount adjustable) |
| | with fan guards and three 75 CFM fans |
| | |

Additional Cooling Equipment, pages 117-122 Additional Power Strips, pages 114-116

MOUNTING RAILS, CASTERS & OTHER ACCESSORIES

| | , CASTERS & OTHER ACCESSORIES |
|------------|--|
| 7205-ES1P | Pair of 19" EIA Mounting Rails with #10-32 tapped holes; includes hardware |
| 7005 5000 | |
| 7205-ES2P | Pair of 19" EIA Mounting Rails to accept M6 cage nuts; |
| | includes hardware |
| HDW-105-50 | Package of 50 M6 cage nuts with screws |
| | (12mm screw length) |
| E23K-36 | Conversion Kit to convert from 19" to 23" mounting |
| G101 | Networking/Ganging Kit |
| AK101 | Seismic Anchor Kit |
| AT2 | Anti-tip Legs |
| 7209-N4 | One set of 4 Adjustable Levelers (4"H); |
| | (When using casters and levelers together, |
| | 4"H levelers are required) |
| 7208-E | One set of 4 Casters, 2 locking and 2 non-locking |
| 7208-EHD | One set of 4 Heavy Duty Casters, all locking |
| 7200 END | (required for 1500 lb. weight capacity) |
| ZR2 | |
| ZRZ | Set of two mounting brackets to allow the vertical |
| | mounting of any 2 RMU equipment (such as cable |
| | organizers) without occupying any RMU space |
| | |