



NOTES: Sealed ball bearing fan  
 Fan blade with Feathered Edge™ for lower noise  
 4 ft. power cord w/5-15P plug per fan

- A) CFM: 550 per fan
- B) VAC: 115 per fan
- C) Hz: 50/60 per fan
- D) Watts: 67/61 per fan
- E) Line Amps: .48/.50 per fan
- F) dBA: 45.4 per fan



INTERPRET DRAWING PER ASME Y14.5M-1994
DIMENSIONAL LIMITS APPLY AFTER APPLICATION OF FINISH
DRAWING NOT TO SCALE
TOLERANCE UNLESS OTHERWISE NOTED:
ANGULAR +/- 1-
.XXXX +/- .010
.XXX +/- .015
.XX +/- .030
X FOR REF. ONLY
UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES

**NOTICE:**  
 Use of this document is subject to a confidentiality and nondisclosure agreement with Great Lakes Case & Cabinet Co., Inc. (GLCC) and may not be reproduced, disclosed or utilized in whole or in part without prior written authorization from GLCC.

PART NUMBER: <b>TPE242F10</b>	
QTY PER UNIT: 1	
MATERIAL TYPE: CRS	
MATERIAL GAUGE: 16 GA	
FINISH: SEE NOTES	
DRAWN WSS	DATE 4/14/2004
CHECKED & APP. WSS	DATE 5-23-05

TITLE <b>ENHANCED TOP PANEL - 2 FAN 10" DIA. 1100CFM</b>	
GREAT LAKES CASE & CABINET CO., INC. P.O. BOX 551 EDINBORO, PA 16412 PHONE (814) 734-7303 FAX (814) 734-3907 E-MAIL glcc@greatcabinets.com	
DWG NO: <b>1001194</b>	REV <b>0</b>
SHEET: 2 OF 2	