

Reentrant Horn Loudspeakers

Models SPT15A and SP158A



Description

The Bogen SPT15A and SP158A are compact, high intelligibility, reentrant type loudspeakers, designed for one-way or two-way sound and communication systems. Their sturdy, weatherproof, all-metal construction is ideal for indoor and outdoor use in industrial plants, warehouses, schools, construction sites, transportation terminals, and recreational areas.

The Model SPT15A has a built-in, rotary impedance selector switch for matching the speaker power requirements to a 25V or 70V constant-voltage line. The model SP158A has an 8-ohm impedance only.

Features

- High intelligibility and efficiency; ideal for both one-way and talk back applications
- Weatherproof, all-metal construction
- 15 watts; 25/70 volt (SPT15A) or 8-ohm (SP158A) operation
- Tap settings for 70V: 15, 7.5, 3.8, 1.8, 0.9 watts; for 25V: 15, 7.5, 1.8, 0.94, 0.46 watts
- Rotary tap impedance selector on SPT15A
- Tilt and swivel base for easy positioning
- Screw terminals make installation fast and easy
- All-purpose mounting bracket
- Self-aligning, field replaceable diaphragm
- Mocha enamel finish
- Limited lifetime warranty
- Mountable to I-beam flange using Bogen's BC1 Beam Clamp (sold separately)
- Mountable to electrical box using Bogen's HSES10 mounting strap (sold separately)
- Terminal Cover (TCSPT1) allows connection of conduit fittings to horn speakers (sold separately)

BOGEN®

Specifications subject to change without notice.
© 1995 Bogen Communications, Inc.
54-7612-05D 0904

Technical Specifications

Power Rating (RMS): 15 watts continuous, 20 watts equalized

Frequency Response: 275 Hz to 14 kHz

Impedance:

SPT15A — 25/70 volts

SP158A — 8 ohms

Sound Pressure Level: 121 dB @ four feet on axis with 15 watt input @ 1000 Hz

Dispersion: 110°

Sensitivity as Microphone: -22 dBm [Ref: 10 dynes/cm²]

Dimensions: 9" Diameter x 9-1/4" D

Product Weight:

SPT15A — 4 lb.

SP158A — 3 lb.

Finish: Textured mocha enamel

Impedance Selector Switch Settings (SPT15A only): 25V @ 15, 7.5, 1.8, 0.94, 0.46 watts
70V @ 15, 7.5, 3.8, 1.8, 0.9 watts

Sound Pressure Level in dB @ 1000Hz:	Watts	Feet on Axis				
		4	8	16	32	64
Input:						
15		121	115	109	103	97
7.5		118	112	106	100	94
3.8		115	109	103	97	91
1.8		112	106	100	94	88
0.9		109	103	97	91	85
0.46		106	100	94	88	82

Architect and Engineer Specifications

The loudspeaker shall be a Bogen Model ____ (specify SPT15A or SP158A), or approved equal, reentrant type horn loudspeaker. The frequency response shall be 275 Hz to 14 kHz. Rated power output shall be 15 watts, RMS continuous. Dispersion shall be 110°. Sound pressure level, measured four feet on axis with 15 watt input @ 1000 Hz, shall be at least 121 dB.

Use for SPT15A. The unit shall incorporate a seven-position weather-sealed switch, to allow matching the loudspeaker to a 25V or 70V constant-voltage line. Power handling capacity shall be adjustable at 70V to 0.9, 1.8, 3.8, 7.5, or 15 watts, and at 25V to 0.46, 0.94, 1.8, 7.5, or 15 watts.

Use for SP158A. The unit shall have an impedance of 8 ohms.

The loudspeaker shall be of weatherproof, all-metal construction, with driver enclosed within a weatherproof housing. The loudspeaker shall include a self-aligning, field-replaceable diaphragm.

Screw terminals shall be provided for connection to the audio line. A plastic cover shall be provided to protect the connectors and impedance selector switch, and provide strain relief for the audio line.

An all-purpose mounting bracket shall provide precise positioning in the vertical and horizontal planes with a single adjustment. The bracket shall include banding slots to permit mounting the loudspeaker on beams or pillars. Bracket and loudspeaker shall be finished in textured mocha enamel. The unit shall measure 9" diameter by 9-1/4" D. Product weight shall be _____ (insert 4 lb. for SPT15A, 3 lb. for SP158A).